


OMR C

Optical mark reader
with automatic feed



Brief specification

Up to 9'000 docs/h
Automatic batch feed
2 sorting output trays

Common options

Barcode reading head
Printer

Example applications

Schools and universities
Hospitals and laboratories
Quality control

About DATAWIN

Development, design and production of high-end documents scanners and OMRs at Ergolding, next to Munich
Worldwide partners and installations
Quality made in Germany: 30 years experience and certified by the European quality norm ISO 9001:2008

A4 optical mark reader with twofold sorting

OMR C is a compact optical mark reader with automatic document feed from a stack and document sorting in two trays.

OMR C processes both sides of up to 250 documents per minute. Possible marking grids are 1/4", 1/5" or 1/6". Depending on the track interval, up to 48 read tracks are possible.

As the little brother of the high-performance device OMR S, the OMR C offers an optimized price-performance ratio for applications in the medium to high capacity spectrum.




Sales & Support in INDIA -

Mark Reader
A-133 Shastri Nagar Delhi-110052
www.omr.in email - info@omr.in
Ph :- 09810392402 ,09971543678

DATAWIN
Data Capturing Solutions

OMR S

Technical Specifications



Document feeding and sorting

- Throughput: up to 9'000 docs/h
- Transporter speed: up to 1,3 m/s
- Automatic batch feed (ADF)
- Stack capacity: max. 650 documents
- Automatic document adjustment
- Double sheet detection: ultra-sonic
- Sorter: 2 guided output trays
- Easy maintenance without tools
- Long-time steady silicon rollers (up to 5 years)

Document dimensions

- Format: min. 124 x 70 mm, max. 430 x 220 mm
- Weight: 60 - 160 g/m²
- Quality: OCR acc. bis DIN 66223

OMR-details

- Optical reading heads redlight or infra red
- 12 to 48-tracks, 1/4", 1/5" und 1/6"
- Dust-proof and self cleaning
- Dynamic self-adjusting (document colours and shades of grey)
- Dynamic reading security in case of dirt
- Insensible against folds and „reflecting markings“
- Multilevel rereading
- DATAWIN and AXIOME-interface compatibility

Interfaces

- USB
- RS232 - Serial Interface
- With embedded PC: Ethernet

Supported OS

- MS Windows 7 (32 and 64 bit)
- MS Windows XP 32 bit

Control panel

- Status-LED
- Optional Touchscreen

Mechanical and power values


- Dimensions: 900 x 500 x 480 mm
- Weight: 30 - 35 kg
- Ambient temperature: +10° C bis 40° C
- Relative humidity: 40 - 60%, condensation free
- Integrated power supply 110 V – 250 V AC
- StandBy 5 W, run 115 W

Standards

- CE, VDE 0805/5.90, VDE 0871-B
- UL-proof
- ISO9001-2008 certified production

Options

- Optical barcode reading head
- OMR-reading head backside
- CIS-camera for image capturing
- Pre/post printer
- Embedded PC
- Long document scanning
- Touchscreen



Sales & Support in INDIA -

Mark Reader

A-133 Shastri Nagar Delhi-110052

www.omr.in email - info@omr.in

Ph :- 09810392402 ,09971543678

DATAWIN
Data Capturing Solutions